

# LT15 CLASSIC WIDE MOBILE

MAX. LOG  
CAPACITY  
90 cm



Pictured: LT15WCS3G25SP-1.5ESWP

## COMPACT SAWMILL IDEAL FOR SAWING WIDE BOARDS

The **LT15CLASSICWIDE Mobile** sawmill has been built based on proven and reliable engineering designs from the proven LT15 models, which have earned worldwide recognition among users. It makes an interesting offer for companies and individuals who need to cut larger logs away from their sawmilling workshops.

### PERFORMANCE SPECIFICATIONS

#### CUTTING CAPACITY

Max. Log Capacity  
90 cm dia.  
x 5.2 m (3 segments 1.95 m each)

Max. Width of Cut 88 cm  
Max. Cant Width 82 cm

#### POWER

Standard 11 kW Electric  
25 HP Petrol

# LT15 CLASSIC

MAX. LOG  
CAPACITY  
70 cm



Pictured: LT15SCS3EH10SP-ESWP

## COMPACT, ECONOMICAL AND RELIABLE SAWMILLING SOLUTION

Incredibly versatile, the LT15 sawmill is very popular because of its high quality, wide capabilities, proven reputation, and affordability.

### PERFORMANCE SPECIFICATIONS

#### CUTTING CAPACITY

Max. Log Capacity  
70 cm dia.  
x 5.2 m (2 segments 2.7 m each)  
x 5.4 m (3 segments 1.95 m each)  
x 7.9 m (3 segments 2.7 m each)

Max. Width of Cut 64 cm  
Max. Cant Width 59 cm

#### POWER

Standard 7.5 kW Electric  
Optional 11 kW Electric  
19 HP Petrol  
10 HP Diesel



### LT15CLASSIC WIDE MOBILE EQUIPMENT



**SW10**  
Simply select the board thickness and the head height automatically positions for each cut.



**Log Clamps**  
Secure logs and allow you to cut as low as 25 mm from the bed.



**Blade tension** is easily adjusted, and keeps the blade at the proper tension for cutting.



Logs are secured onto the bed by six **Side Supports**.



**Debarker**  
Extends blade life by clearing the blade path of dirt and rocks.



**Mobile trailer**  
Includes adjustable outrigger supports for stability on any terrain.

### LT15CLASSIC WIDE MOBILE SPECIFICATIONS

#### Sawmill Head Features & Options

Standard	Electric up/down (screw) Manual blade guide arm Blade lubrication system
Options	SW10 Setworks Debarker Electric power feed

#### Sawmill Bed Features & Options

Standard	S3 bed: 6 Side supports + 3 Manual log clamps Log wedge Mobile trailer (weight: 1500 kg)
Options	Log loading ramps with winch

#### Blade

Length	4470mm
Width	32 mm - 35 mm
Blade wheel diameter	483 mm (belted)



### LT15CLASSIC EQUIPMENT



**SW10**  
Simply select the board thickness and the head height automatically positions for each cut.



**Log Clamps**  
Secure logs and allow you to cut as low as 25 mm from the bed.



**Side Supports**  
All six side supports have NEW heavy-duty rollers to assist with log turning.



**Log Wedge** allows you to level tapered logs to ensure maximum recovery.



**Debarker**  
Extends blade life by clearing the blade path of dirt and rocks.



**Electric Power Feed**  
Increase production by adding power feed forward/reverse.

### LT15CLASSIC SPECIFICATIONS

#### Sawmill Head Features & Options

Standard	Electric up/down (screw) Hand crank feed system Manual blade guide arm Blade lubrication system
Options	SW10 Debarker (for AC and DC Petrol model) Electric power feed

#### Sawmill Bed Features & Options

Standard	S3 bed: 6 Side supports + 3 Manual log clamps M2 bed: 4 Side supports + 2 Manual log clamps Log wedge
Options	Additional bed section: 1.95 m or 2.7 m Log loading ramps Cant hook Log moulder/planer MP100 or MP150

#### Blade

Length	4010 mm
Width	32 mm - 35 mm
Blade wheel diameter	483 mm (belted)

Pictured:  
**Compact**  
for shipment



## LT15 CLASSIC MOBILE

MAX. LOG  
CAPACITY  
70 cm



Pictured: LT15CLASSIC MOBILE

### COMPACT, ECONOMICAL AND MOBILE SAWMILLING SOLUTION

Engineered to saw logs directly on the trailer, **LT15CLASSIC MOBILE** extends the LT15 series of sawmills. Perfect solution for woodworkers looking for a mobile and economical sawmill. Now the redesigned trailer allows sawing without the need to remove the wheels and axle. Towing is made safe thanks to a stiffer bed and head security pin. With **LT15CLASSIC MOBILE** produce your timber on the spot!

#### PERFORMANCE SPECIFICATIONS

##### CUTTING CAPACITY

Max. Log Capacity	70 cm dia. x 5.2 m (3 segments 1.95 m each)
Max. Width of Cut	64 cm
Max. Cant Width	59 cm

##### POWER

Standard	7.5 kW Electric
Optional	11 kW Electric
	10 HP Diesel
	19 HP Petrol

## LT15 START MOBILE

MAX. LOG  
CAPACITY  
70 cm



Pictured: LT15START MOBILE

### ULTRA-COMPACT AFFORDABLE MOBILE SAWMILL

Saw logs into timber boards with the **LT15START MOBILE** wherever you go. Ideal solution for woodworkers looking for an affordable and mobile sawmill. The redesigned trailer allows for sawing on the bed without the need to remove the axle and trailer system. Towing is made safe thanks to upgraded and stiffer bed sections and a pin securing the head for transportation.

#### PERFORMANCE SPECIFICATIONS

##### CUTTING CAPACITY

Max. Log Capacity	70 cm dia. x 4.8 m (3 segments 1.95 m each)
Max. Width of Cut	64 cm
Max. Cant Width	59 cm

##### POWER

Standard	5.5 kW Electric
	7.5 kW Electric
	14 HP Petrol



**LT15CLASSIC MOBILE EQUIPMENT**



**SW10**  
Simply select the board thickness and the head height automatically positions for each cut.



**Log Clamps**  
Secure logs and allow you to cut as low as 25 mm from the bed.



**Blade tension** is easily adjusted, and keeps the blade at the proper tension for cutting.



Logs are secured onto the bed by six **Side Supports**.



**Debarker**  
Extends blade life by clearing the blade path of dirt and rocks.



**Mobile trailer**  
Includes adjustable outrigger supports for stability on any terrain.

**LT15CLASSIC MOBILE SPECIFICATIONS**

**Sawmill Head Features & Options**

Standard	Electric up/down (screw) Hand crank feed system Manual blade guide arm Blade lubrication system
Options	SW10 Setworks Debarker Electric power feed

**Sawmill Bed Features & Options**

Standard	S3 bed: 6 Side supports + 3 Manual log clamps Log wedge Mobile trailer (weight: 1300 kg)
Options	Log loading ramps with winch

**Blade**

Length	4010 mm
Width	32 mm - 35 mm
Blade wheel diameter	483 mm (belted)



**LT15START MOBILE EQUIPMENT**



**Manual Feed and Up/Down** Adjust blade height with the crank up/down and gently push the blade into the cut.



**Log Clamps**  
Secure logs and allow you to cut as low as 25 mm from the bed.



**High Quality Blade Rollers**  
Fully adjustable and high quality guides



Logs are secured onto the bed by six **Side Supports**.



**Blade lubrication system**



**Mobile trailer**  
Includes adjustable outrigger supports for stability on any terrain.

**LT15START MOBILE SPECIFICATIONS**

**Sawmill Head Features & Options**

Standard	Hand crank up/down Hand crank feed system Up/Down chain Manual blade guide arm Blade lubrication system
Options	Electric power up/down (screw)

**Sawmill Bed Features & Options**

Standard	S3 bed: 6 Side supports + 3 Manual log clamps Log wedge Mobile trailer (weight: 750 kg)
Options	Log loading ramps with winch

**Blade**

Length	4010 mm
Width	32 mm - 35 mm
Blade wheel diameter	483 mm (belted)

# LT15START

## ULTRA-COMPACT SAWMILL FOR MAXIMUM QUALITY AND AFFORDABILITY

The LT15START is the ideal affordable sawmill for straightforward timber processing with sturdy construction and simple features.



Pictured: LT15SAS3EH7-SP

### PERFORMANCE SPECIFICATIONS

#### CUTTING CAPACITY

Max. Log Capacity

- 70 cm dia.
- x 5.2 m (2 segments 2.7 m each)
- x 5.4 m (3 segments 1.95 m each)
- x 7.9 m (3 segments 2.7 m each)

Max. Width of Cut 64 cm

Max. Cant Width 59 cm

#### POWER

- Standard 5.5 kW Electric
- Optional 7.5 kW; 11 kW Electric
- 14 HP Petrol

# MP100/150

## PLANE AND MOULD HIGH QUALITY FINISHED TIMBER BEAMS

Expand your business with the MP100 and begin the production of moulded/planed timber products. The MP100 is a specialized moulder head that planes rough wood surfaces smooth and moulds patterns to create columns or interlocking beams,



Pictured: MP100EH55-1 together with LT15SCS3EH15EP-E



**LT15START EQUIPMENT**



**Electric power up/down**  
For additional productivity, add the optional electric head up/down.



**Manual log clamp**  
Secures logs and allows you to cut as low as 25 mm from the bed.



**Mould & Plane**  
By adding the MP100 moulding / planing head to the sawmill.

**LT15START SPECIFICATIONS**

**Sawmill Head Features & Options**

Standard	Hand crank up/down Hand crank feed system Manual blade guide arm Blade lubrication system
Options	Electric power up/down (screw)

**Sawmill Bed Features & Options**

Standard	S3 bed: 6 Side supports + 3 Manual log clamps M2 bed: 4 Side supports + 2 Manual log clamps Log wedge
Options	Additional bed section: 1.95 m or 2.7 m Log loading ramps Cant hook Log moulder/planer MP100/MP150

**Blade**

Length	4010 mm
Width	32 mm - 35 mm
Blade wheel diameter	483 mm (belted)



Pictured:  
**Compact**  
for shipment



**MP100/150 EQUIPMENT**



**SW10**  
Simply select the board thickness required and the head height automatically positions for each cut. (available for MP150 only)



**Knife Roller**  
Profile knives slide in and lock into place.



**Secure beam clamps**  
Specialised clamps for holding beams for cutting without damaging high quality surfaces. Cuts as close as 25 mm from the bed are possible.

**SPECIFICATIONS**

	MP100	MP150
Electric motor	4 kW	4 kW
Log feed and up/down	Manual	Electric
Shaft speed	4890 rpm	4890 rpm
Maximum moulding / planing width	410 mm	410 mm
Number of knives	4	4
Minimum material height	60 mm	60 mm
Maximum material height	600 mm	600 mm
Maximum material width	520 mm	520 mm
Standard	-	SW Networks



Pictured: **MP100**  
on optional bed